

• THE TOUGHEST • PERFORMER • • *** FOR YOUR FIELD *** •





















EATURES	≥50 CABIN
TL ENGINE 🕳	
o. of cylinders / capacity (cc) / valves / emissions level	3/ 3065/ 4/ CRDi Stage V
fter treatment system	DOC + DPF
ated engine power (kw/Hp)	37.3/50
ated engine speed	2000
ax. torque (Nm)	220@1400 Rpm
spiration	Turbo charged
tercooler	Yes
r Cleaner	Dual Stage Dry Type
odraft Exhaust Pipe	Yes
uel tank capacity (L)	72
RANSMISSION #	
2x12 Synchro Shuttle transmission (4WD)	Yes
Maximum forward speed	1.3kmph
Minimum forward speed	30kmph
RONT AXLE	
ND Front Axle	Yes
fferential Lock	Mechanical
VD Actuation	Mechanical
ake Actuation	Mechanical Assist
TO ()—	
TO Type	Mechanical
0/540E	Yes
DRAULIC O-	
draulic pump flow (lpm)	45
pen center mechanical draft control	Yes
p link draft sensing	Yes
ftomatic system	Yes
ft Capacity	2500 KG
nkage Category	II
ax. no. of rear remotes	2/3 (0)
ax. no. of Mid remotes	2
EAR HITCHES	
Mark Swinging Drawbar	Yes
RAILER BRAKES	
ithout Trailer Brakes	Yes
ECTRICALS (F)	
uttery	110AH 800CCA
ternator	90A/120A
utton Operated Battery Cut off Switch, 3 Pinsocket, Seven On	Yes
-11011	
ailer Socket	

FEATURES	≶50 cabin
DIMENSIONS 💑	
Wheelbase (mm)	2225
Overall Height (mm)	2690/2480
Overall Width (mm)	1840-1880
Overall Length (mm)	3825-4055
Front Track Width (mm)	1570
Rear Track Width (mm)	1450
Ground Clearance (mm)	310
Unladen Mass (Kg)	2870
Tyre Combination	9.5x20 & 13.6x28

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP

INTERNATIONAL TRACTORS LIMITED